





Features

- ◆ 650V, 16A, $R_{DS(ON)}$ (Max.) = 0.55Ω@VGS = 10V.
- ◆ Low Crss
- ◆ Fast Switching
- ◆ 100% Avalanche Tested



Application

- ◆ Adapter
- ◆ Standby Power
- ◆ Switching Mode Power Supply



Absolute Maximum Ratings $T_c = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Limit	Unit
V_{DS}	Drain-Source Voltage ^a	650	V
V_{GS}	Gate-Source Voltage	± 30	V
I_D	Drain Current-Continuous, $T_c = 25^\circ\text{C}$	16	A
	Drain Current-Continuous, $T_c = 100^\circ\text{C}$	10.6	A
I_{DM}	Drain Current-Pulsed ^b	64	A
P_D	Maximum Power Dissipation @ $T_j = 25^\circ\text{C}$	65	W
EAS	Single Pulsed Avalanche Energy ^d	605	mJ
T_j, T_{STG}	Operating and Store Temperature Range	-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-Case Max.	2.4	°C/W

Electrical Characteristics $T_j = 25^\circ\text{C}$ unless otherwise noted

Off Characteristics

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu\text{A}$	650	-	-	
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 650V, V_{GS} = 0V$	-	-	1	μA
I_{GSS}	Forward Gate Body Leakage Current	$V_{DS} = 0V, V_{GS} = \pm 30V$	-	-	± 100	nA

On Characteristics



Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 250\mu A$	2	-	4	V
$R_{DS(on)}$	Static Drain-Source On-Resistance ^c	$V_{GS} = 10V$, $I_D = 8.0A$	-	0.45	0.55	Ω

■ Dynamic Characteristics

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
g_{fs}	Forward Transconductance ^d	$V_{DS} = 15V$, $I_D = 8.0A$		15		S
C_{iss}	Input Capacitance		-	2430	-	pF
C_{oss}	Output Capacitance		-	215	-	pF
C_{rss}	Reverse Transfer Capacitance		-	18	-	pF

■ On Characteristics

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-On Delay Time	$V_{DD} = 325V$, $I_D = 16A$, $R_G = 25\Omega$, $V_{GS} = 10V$	-	28	-	ns
t_r	Turn-On Rise Time		-	68	-	ns
$t_{d(off)}$	Turn-Off Delay Time		-	142	-	ns
t_f	Turn-Off Fall Time		-	73	-	ns
Q_g	Total Gate Charge	$V_{DS} = 325V$, $I_D = 16A$, $V_{GS} = 10V$	-	53		nC
Q_{gs}	Gate-Source Charge		-	11	-	nC
Q_{gd}	Gate-Drain Charge		-	23	-	nC

■ Drain-Source Diode Characteristics

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
I_s	Drain-Source Diode Forward Continuous Current	$V_{GS} = 0V$	-	-	16	A
I_{SM}	Maximum Pulsed Current	$V_{GS} = 0V$	-	-	64	A
V_{SD}	Drain-Source Diode Forward Voltage	$V_{GS} = 0V$, $I_s = 16A$	-	0.9	1.4	V

Notes:

- a. $T_J = -55^\circ C$ to $+150^\circ C$
- b. Repetitive rating; pulse width limited by maximum junction temperature.
- c. Pulse width $\leq 300\mu s$; duty cycle $\leq 2\%$
- d. $L = 10mH$, $V_{DD} = 50V$, $I_{as} = 11.0A$, $R_G = 25\Omega$ Starting $TJ = 25^\circ C$




Figure 1 Maximum Safe Operating Area




Figure 2 Normalized On-Resistance Variation with Temperature




Figure 3. Typical Threshold Voltage vs Junction Temperature




Figure 4. Capacitance Characteristics




Figure 5. Gate Charge Characteristics




Figure 6. On-State Characteristics




Figure 7. Typical Body Diode Transfer Characteristics




Figure 8. Typical Breakdown Voltage vs Junction Temperature




Figure 9. Normalized Effective Transient Thermal Impedance With Pulse Duration(TO-220F)